

Monocrystalline Photovoltaic Module »



MEPV 144 HALF-CUT PLUS

STANDARD » 550 W_p

QUALITY »



MBB technology
Better light absorption



Reduced BOS
Cost effective product



+5W
Positive power tolerance



Fire resistance
Maximum protection



Avoid losses
Better shading tolerance



Efficiency
Over 20% efficiency



WARRANTIES »

15 YEARS PRODUCT WARRANTY

25 YEARS PERFORMANCE WARRANTY
Linear Warranty

PRODUCT WARRANTY
for Premium Partners

+5
YEARS

CERTIFICATES »



TECHNICAL FEATURES »

Eurener_MEPV 144_HALF-CUT PLUS_550Wp_2022EN

FRAME

Silver anodized aluminium

Robust and resistant to corrosion

CONNECTION BOX AND PROTECTIONS

Sealed, robust and wide for heat dissipation

IP67/IP68 according to IEC 60529

Diodes by-pass built-in (3/6)

Connector MC4 compatible

Application Class A. Safety Class II

Cables 1000 mm ($\pm 20\%$) length and 4 mm² section

FRONTAL

3,2 mm thick tempered glass with high strength and ARC

Textured, extra-clear with low iron content



Frontal load (snow) 5400 Pa | Back load (wind) 2400 Pa

SOLAR CELLS

144 [2x(12x6)] cells monocrystalline silicon

WEIGHT, DIMENSIONS AND PACKAGING

27,4 Kg | 2279 x 1134 x 35 mm ($\pm 1\%$) | Pack: 620 pcs-truck



ELECTRIC DATA »

STANDARD	MEPV 550
STC: 1000 W/m ² , module temperature 25°C, AM 1,5	
Nominal power. P _{mpp}	550 Wp
Tolerance. P _{mpp}	0 / +5 W
Area of the module	2,58 m ²
Module efficiency	21,30 %
I _{sc}	13,93 A
V _{oc}	49,97 V
I _{mpp}	13,12 A
V _{mpp}	41,95 V
NOCT: 800 W/m ² , ambient temperature 20°C, AM 1,5	
Nominal power. P _{mpp}	415,49 W
I _{sc}	11,22 A
V _{oc}	47,17 V
I _{mpp}	10,50 A
V _{mpp}	39,57 V
Operating parameters. Temperature coefficients	
Maximum voltage	1000 - 1500 V
Maximum series fuse rating. I _r	25 A
α I _{sc}	0,047 % / °C
β V _{oc}	- 0,27 % / °C
γ P _{max}	- 0,34 % / °C
Temperature range	- 40°C ~ + 85 °C
NOCT	44 \pm 2 °C

NOTE: Read the instruction manual of this product and follow the indications STC. Values are valid for: 1000W/m², AM 1,5 and cells temperature of 25°C. Measurement tolerance +/-3% (AAA Solar simulation -IEC 60.904-9-). All the information of this brochure may be amended without notice by Eurener. Eurener_MEPV 144_HALF-CUT PLUS_550Wp_EN_JUN2022

1997 to 2022
25
TH
ANNIVERSARY

www.eurenergroupp.com
contact@eurenerworld.com
+34 960 045 515
Calle Colón, 1-23
46004, Valencia. Spain

25 years manufacturing a better world

Since 1997 our main purpose has been to supply quality and long-lasting photovoltaic modules that allow us and future generations, to continue generating clean energy to take care of our planet.